

Cemimax DL24 Self-leveling Compound

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Cemimax New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Cemimax DL24 Self-leveling Compound
Line	Self-leveling Compound for thickness from 2mm to 15mm
Identifier	

Description

DL24 is an advanced cement and polymer based levelling and smoothing compound. Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

Scope of use

- DL24 is formulated for leveling work on standard construction in universal areas.
 - DL24 is very suitable for normally traffic, quick-setting and economical surface preparation solutions.
 - DL24 can be applied from 2mm to 15mm thickness in one application.
-

Conditions of use

Subfloor Preparation

- The substrate must be sound, free from cracks, dry, clean and free from materials which would impair adhesion.
- Test the substrate according to applicable standards and report any deficiencies.
- Brush, abrade, grind or shot-blast any weak surface sections or areas which will not accept adhesion.
- Thoroughly vacuum to remove loose material and dust. According to type and condition of the subfloor, suitable primer.
- Allow primers to dry thoroughly.

Application

- Put 4.8-5.2 litres of cold clean water into a clean container. Sprinkle in the sack contents (20kg) whilst stirring briskly and mix to a thick-fluid. Lump-free consistency. Use a drill or mixer fitted with a Mixing Paddle. Do not mix too thinly. For best flow ability of product, mix for 3 mins.
- Pour the mixture on the area to be applied, spread the material uniformly to Required thickness using toothed rake. It is the next step to remove entrapped air by particular roller.
- Drying time at 20°C is approx 24 hours. Abrading using 40-60 grit sanding paper improves both the surface quality and the absorbency. Poor air-flow and lower temperatures will significantly affect drying times.

Contributions to compliance

B2.3.1(b) (ii) Cemimax DL24 has durability of at least 15 years. F2.3.1 Cemimax DL24 is safe when handled correctly as per Application Instructions on TDS.

Supporting documentation

The following additional documentation supports the above statements:

None added

For further information supporting Cemimax DL24 Self-leveling Compound claims refer to our website.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Cemimax Australia Pty Ltd

Legal and trading name of importer	Cemimax New Zealand Limited
Importer address for service	23A Canaveral Drive, Rosedale Auckland 0632
Importer website	
Importer NZBN	9429051766979
Importer email	info@cemimax.co.nz
Importer phone number	02102313450

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Cemimax DL24 Self-leveling Compound is not subject to a warning on ban under [s26 of the Building Act](#).

Signed for and on behalf of **Cemimax New Zealand Limited**:



Jeff Xu

Director

June 2026



CEMIMAX NEW ZEALAND LIMITED
23A Canaveral Drive, Rosedale Auckland 0632 New Zealand.
02102313450 | info@cemimax.co.nz