

# CEMIMAX DL33 Self-smoothing and Leveling Compound

## BPIR Declaration

Version: V1

---

### Designated building product: Class 1

---

### Declaration

Cemimax New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

### Product/system

<b>Name</b>	CEMIMAX DL33 Self-smoothing and Leveling Compound
<b>Line</b>	Self-leveling Compound for thickness from 1.5mm to 100mm
<b>Identifier</b>	

---

### Description

Product Properties/Benefits:

Plastic dry cement mortar with finely graded fillers. When mixed with water, produces a hydraulic-setting smoothing compound with good flow properties and high coverage.

Composition:

Special cements, mineral fillers, polyvinyl-acetate-copolymers, flow agents and additives

- Super smooth - requires no sanding

- Versatile - apply 1.5mm to 100mm in one application
  - Rapid hardening - walkable from 2 hours
  - Superior flow - fast application
  - Flexible - hand mix or pump application
- 

## Scope of use

- D33 is formulated for leveling work on standard construction in level large commercial and retail areas.
  - DL33 is very suitable for normally traffic, quick-setting and economical surface preparation solutions.
  - DL33 can be applied from 1.5mm to 100mm thickness in one application.
- 

## Conditions of use

### Substrate Preparation:

The substrate must be sound, load bearing, dry, free from cracks and free from materials (dirt, oil, grease) that would impair adhesion. Cement and calcium sulphate screeds must be abraded and vacuumed. Test the substrate in accordance with applicable standard or notices and report any deficiencies.

Any adhesion-reducing or unstable layers, e.g. release agents, loose adhesives, compounds, covering or paint residues, etc. must be removed, e.g. by brushing, abrading, grinding or shot blasting. Thoroughly vacuum loose material and dust. Use a suitable primer according to the type and condition of the substrate. Allow any primer that is applied to dry completely.

The data sheets for other used products must be observed.

### Application:

- Put 4.6-4.8 liters of cold clean water into a clean container. Sprinkle in the sack contents (20kg) whilst stirring briskly and mix to a thick fluid. Lump-free consistency. Use a drill or mixer fitted with a Mixing Paddle. Do not mix too thinly.
- Pour the mixture on the area to be applied, spread the material uniformly to Required thickness using toothed rake. It is the nextstep to remove entranced air by particular roller.
- Drying time at 20°C is approx. 24 hours. Abrading using 40-60 grit sanding paper improves both the surface quality and the absorbency. Poor airflow and lower temperatures will significantly affect drying times.

---

## Contributions to compliance

B2.3.1(b) (ii) Cemimax DL33 has durability of at least 15 years. F2.3.1 Cemimax DL33 is safe when handled correctly as per Application Instructions on TDS.

---

## Supporting documentation

For further information supporting CEMIMAX DL33 Self-smoothing and Leveling Compound claims refer to our website.

---

## Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Cemimax Australia Pty Ltd
Legal and trading name of importer	Cemimax New Zealand Limited
Importer address for service	23A Canaveral Drive, Rosedale Auckland 0632
Importer website	
Importer NZBN	9429051766979
Importer email	info@cemimax.co.nz
Importer phone number	02108182015

---

## Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that CEMIMAX DL33 Self-smoothing and Leveling Compound is not subject to a warning on ban under [s26 of the Building Act](#).

Signed for and on behalf of **Cemimax New Zealand Limited**:

Jeff Xu

Jeff Xu

Director

June 2026



---

**CEMIMAX NEW ZEALAND LIMITED**  
23A Canaveral Drive, Rosedale Auckland 0632 New Zealand  
02102313450 | [info@cemimax.co.nz](mailto:info@cemimax.co.nz)

# Appendix

Note: The below appendix includes information relating to BPIR Ready.

Publishing this information is not a requirement under BPIR. Its inclusion here is to provide a reference for how this BPIR summary was generated as well as to help summary creators understand the performance clauses suggested by BPIR Ready.

---

## BPIR Ready selections

Category: Other (custom)

---

## Building code performance clauses