

Cemimax DL59 Bi Turbo Self-leveling Compound

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Cemimax New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Cemimax DL59 Bi Turbo Self-leveling Compound
Line	60mins fast-setting self-leveling compound for thickness from 1.5 to 40mm
Identifier	

Description

DL59 Bi Turbo is a highly polymer-modified, fast-setting self-leveling compound that will accept floor covering in approximately 60 minutes. It is sufficiently dry for installation of most floor coverings as soon it is set to walk on, allowing for complete renovations in a single day.

Scope of use

- Ready for floor covering installation in 2-3 hours.
- Applies from 1.5 mm to 40mm in one application.
- For installation of most floor coverings as soon it is set to walk on, allowing for complete renovations in a single day.

Conditions of use

Subfloor Preparation:

- The substrate must be sound, free from cracks, dry, clean and free from materials which would impair adhesion.
- Test the substrate according to applicable standards and report any deficiencies.
- Brush, abrade, grind or shot blast any weak surface sections or areas which will not accept adhesion.
- Thoroughly vacuum to remove loose material and dust.
- Use a suitable primer according to the type and condition of the substrate. Allow any primer that is applied to dry completely.

Application:

- Put 4.25-4.5litres of cold clean water into a clean container. Sprinkle in the sack contents (20kg) whilst stirring briskly and mix to a thick fluid. Lump-free consistency. Use a drill or mixer fitted with a Mixing Paddle. Do not mix too thinly.
- Pour the mixture on the area to be applied, spread the material uniformly to required thickness using toothed rake. It is the next step to remove entranced air by particular roller.

- Drying time at 20°C is approx., 24 hours. Abrading using 40-60 grit sanding paper improves both the surface quality and the absorbency. Poor airflow and lower temperatures will significantly affect drying times.

Contributions to compliance

B2.3.1(b) (ii) Cemimax DL59 Bi Turbo has durability of at least 15 years. F2.3.1
Cemimax DL59 Bi Turbo is safe when handled correctly as per Application
Instructions on TDS.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Cemimax Australia Pty Ltd
Legal and trading name of importer	Cemimax New Zealand Limited
Importer address for service	23A Canaveral Drive, Rosedale Auckland 0632
Importer website	
Importer NZBN	9429051766979
Importer email	info@cemimax.co.nz
Importer phone number	02102313450

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Cemimax DL59 Bi Turbo Self-leveling Compound is not subject to a warning or ban under [s26 of the Building Act](#).

Signed for and on behalf of **Cemimax New Zealand Limited**:



Jeff Xu

Director

June 2026



CEMIMAX NEW ZEALAND LIMITED

23A Canaveral Drive, Rosedale Auckland 0632 New Zealand

02102313450 | info@cemimax.co.nz