

# Cemimax DP400

## BPIR Declaration

Version: V1

---

### Designated building product: Class 1

---

### Declaration

Cemimax New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

---

### Product/system

<b>Name</b>	Cemimax DP400
<b>Line</b>	2K Epoxy Resin Moisture Vapor Retarder and Surface Hardening Primer
<b>Identifier</b>	

---

### Description

Cemimax DP400 is a 2-component solvent free Epoxy resin primer used to improve the strength of the substrates. It can be used as crack repair for concrete, cement-based subfloors. It can also be used as moisture vapor retarder for concrete substrates with high residual moisture.

## Scope of use

Especially suitable for use on substrates with low damp conditions, on ceramic, terrazzo, stone subfloors, surfaces with well-bonded waterproof adhesive and smoothing compound residues. Use on cracked substrates as a repair resin.

- Bridges cracks
- Moisture controls up to 100% RH
- Increase the strength of the substrate
- Very good resistance to chemical
- Excellent covering and filling capacity
- Solvent free

---

## Conditions of use

- The subfloor must be sound, surface dry (no pooling, remove standing water), free from cracks, clean and free from materials that would impair adhesion.
- Test the subfloor in accordance with applicable standards and notices and report any deficiencies.
- Depending on subfloor condition, the upper surface must have a good key provided in all cases.
- Brush, abrade, grind or shot blast to remove any weak or soft surface layers, e.g. soft screed edges, hard sinter, separating agents, loose residues of adhesives, smoothing compounds, coverings or coatings.
- Then thoroughly vacuum.
- After mixing A and B components stir the materials fully.
- Apply the primer evenly to fully cover the surface using a fine-pored foam roller cross-stroke.
- At the same time throwing the quartz sand (70-140#) on applied primer surface. Sand consumption by 0.5-1kg/m<sup>3</sup>.
- The next day can be application of leveling compound.
- When used as a moisture barrier, a minimum of two coats is recommended. Apply the second coat as soon as the first will accept foot traffic, not later than 24 - 36hours.

---

## Contributions to compliance

B2.3.1(b) (ii) Cemimax DP400 has durability of at least 15 years. F2.3.1 Cemimax DP400 is safe when handled correctly as per Application Instructions on TDS.

---

## Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Cemimax Australia Pty Ltd
Legal and trading name of importer	Cemimax New Zealand Limited
Importer address for service	23A Canaveral Drive, Rosedale Auckland 0632
Importer website	
Importer NZBN	9429051766979
Importer email	info@cemimax.co.nz
Importer phone number	02102313450

---

## Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Cemimax DP400 is not subject to a warning on ban under [s26 of the Building Act](#).

Signed for and on behalf of **Cemimax New Zealand Limited**:

A handwritten signature in black ink that reads "Jeff Xu". The letters are cursive and fluid.

Jeff Xu

Director

June 2026



---

**CEMIMAX NEW ZEALAND LIMITED**

23A Canaveral Drive, Rosedale Auckland 0632 New Zealand

[02102313450](tel:02102313450) |