

Cemimax DP80

BPIR Declaration

Version: V1

Designated building product: Class 1

Declaration

Cemimax New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Cemimax DP80
Line	Non-porous primer
Identifier	

Description

DP 80 is a water based, very low emission, acrylic, dispersion, film forming primer that enhances the performance and bonding of Cemimax Self-Leveling products that are to be installed over existing well bonded flooring (quarry, porcelain, and ceramic tile; VCT, Sheet Vinyl; Terrazzo; Metal Decking, and Rubber), and well bonded non-water soluble adhesive residue. It can also be used directly over Cemimax high-quality 100% solids epoxy and polyurethane (PU) based primers/ moisture vapor retarders (MVR)/ barriers.

Scope of use

- Installed over all existing flooring that must be structurally sound, solid, thoroughly clean and free of polishes, waxes, grease, asphalt and any other contaminant that might act as a bond breaker.
- Can be applied over properly prepared and installed 100% solids epoxy moisture barriers and PU vapor retarders, Epoxy cement terrazzo and poured epoxy or PU flooring.
- Dimensionally stable moisture resistant, exterior grade plywood.
- For use where Radiant Heat systems are being installed.
- Existing surfaces in need of refurbishment, such as well bonded, non-water-soluble adhesive residues including cutback.

Conditions of use

Substrate preparation:

- The subfloor should be thoroughly cleaned, dry, free of debris, and no loosely bonded surfaces. Make sure there are no active cracks, completely free of contaminants like curing compounds, solvent based markers or paint, oil, grease, and wax that would block absorption into the substrate.
- Test substrate in accordance with applicable standards relative to moisture content.
- Any weakly bonded material such as adhesive residue, leveling compounds, floor coverings or coatings must be removed by shot blasting, abrading, grinding, or scraping.
- Do not apply over water-soluble adhesive. If applying over an MVR it must be properly installed following the installation instructions.

Application:

- Do not dilute with water.

- Thoroughly stir container for until all settled clumps are off the bottom and suspended in the liquid.
- This product should be applied in a full, even, thin coat by rolling it on with a 3/4 nap nylon. Being careful not to leave any puddling behind at the roller edges as it will delay the drying of the primer and could cause issues with bonding.
- Allow to dry to a clear, transparent, almost tack-free film. When dry you should be able to feel almost sandpaper like feel on the substrate. Drying time for the DP 80 is about 20 min to an hour in cold humid climates.
- Clean equipment immediately with water. Mineral spirits may be used to remove primer that has dried on tools.

Contributions to compliance

B2.3.1(b) (ii) Cemimax DP80 has durability of at least 15 years. F2.3.1 Cemimax DP80 is safe when handled correctly as per Application Instructions on TDS.

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Cemimax Australia Pty Ltd
Legal and trading name of importer	Cemimax New Zealand Limited
Importer address for service	23A Canaveral Drive, Rosedale Auckland 0632
Importer website	
Importer NZBN	9429051766979

Importer email	info@cemimax.co.nz
Importer phone number	02102313450

Responsible person

As the responsible person as set out in Regulation 3, I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm that Cemimax DP80 is not subject to a warning on ban under [s26 of the Building Act](#).

Signed for and on behalf of **Cemimax New Zealand Limited**:



Jeff Xu

Director

June 2026



CEMIMAX NEW ZEALAND LIMITED

23A Canaveral Drive, Rosedale Auckland 0632 New Zealand

02102313450 | info@cemimax.co.nz